



City of Santa Clara  
Building Division  
1500 Warburton Ave.  
Santa Clara, CA 95050  
www.santaclaraca.gov

Building Division: 408-615-2440  
Email: Building@santaclaraca.gov  
Permit Center: 408-615-2420  
Email: PermitCenter@santaclaraca.gov  
Automated Inspection Scheduling System: 408-615-2400

## 2016 CALIFORNIA BUILDING CODE - SECTION 11B-208, 11B-501 & 11B-502 GENERAL REQUIREMENTS FOR ACCESSIBLE PARKING


### ❖ NUMBER OF PARKING SPACES (Table 11B-208.2)

Total Number of Parking Spaces Provided	Minimum Number of Accessible Spaces Required
1-25	1 (1 Van min.)
26-50	2 (1 Van min.)
51-75	3 (1 Van min.)
76-100	4 (1 Van min.)
101-150	5 (1 Van min.)
151-200	6 (1 Van min.)
201-300	7 (2 Van min.)
301-400	8 (2 Van min.)
401-500	9 (2 Van min.)
501-1000	2% of total (1 Van for every 6 Accessible Parking)
1001 & Over	20+1 for each 100, or fraction thereof (1 Van for every 6 van accessible Parking per CBC 11B-208.2.4)

#### Note:

- Hospital outpatient facilities:** required accessible spaces shall be 10% of the total spaces.
- Rehabilitation facilities and outpatient physical therapy facility** (specializing in treating conditions that affect mobility): required accessible spaces shall be 20% of the total spaces.

### ❖ PARKING SPACE SIZE AND LAYOUT



**FIGURE: SINGLE ACCESSIBLE PARKING STALL**




City of Santa Clara  
Building Division  
1500 Warburton Ave.  
Santa Clara, CA 95050  
www.santaclaraca.gov

Building Division: 408-615-2440  
Email: Building@santaclaraca.gov


Permit Center: 408-615-2420  
Email: PermitCenter@santaclaraca.gov

Automated Inspection Scheduling System: 408-615-2400

## 2016 CALIFORNIA BUILDING CODE - SECTION 11B-208, 11B-501 & 11B-502 GENERAL REQUIREMENTS FOR ACCESSIBLE PARKING



**FIGURE: DOUBLE ACCESSIBLE PARKING STALL**



**FIGURE: DIAGONAL ACCESSIBLE PARKING STALL**




City of Santa Clara  
Building Division  
1500 Warburton Ave.  
Santa Clara, CA 95050  
www.santaclaraca.gov

Building Division: 408-615-2440  
Email: Building@santaclaraca.gov  
Permit Center: 408-615-2420  
Email: PermitCenter@santaclaraca.gov  
Automated Inspection Scheduling System: 408-615-2400

## 2016 CALIFORNIA BUILDING CODE - SECTION 11B-208, 11B-501 & 11B-502 GENERAL REQUIREMENTS FOR ACCESSIBLE PARKING


### ❖ Parking Space Signage



### PARKING SIGNAGE PER CBC 11B-502.6

### ADDITIONAL SIGNAGE PER CBC 11B-502.8

### ❖ ILLEGAL Built-up Curb Ramps at Disabled Parking Stalls



### ILLEGAL BUILT-UP CURB RAMPS AT DISABLED PARKING STALLS



City of Santa Clara  
Building Division  
1500 Warburton Ave.  
Santa Clara, CA 95050  
www.santaclaraca.gov

Building Division: 408-615-2440  
Email: Building@santaclaraca.gov  
Permit Center: 408-615-2420  
Email: PermitCenter@santaclaraca.gov  
Automated Inspection Scheduling System: 408-615-2400

## 2016 CALIFORNIA BUILDING CODE - SECTION 11B-208, 11B-501 & 11B-502 GENERAL REQUIREMENTS FOR ACCESSIBLE PARKING


### ❖ Passenger Drop-Off and Loading Zone Access Aisle

#### When Required

- Passenger Drop-Off & Loading Zone:** Provide at least one accessible passenger drop-off and loading zone complying with CBC 11B-503 in every continuous 100 linear feet of drop-off and loading zone space. (CBC11B-209.2.1)
- Valet Parking:** Parking facilities that provide valet parking services shall provide at least one accessible passenger drop-off and loading zone complying with CBC 11B-503 at vehicle drop-off and vehicle pick-up areas. (CBC11B-209.2.1)
- Mechanical Access Parking Garages:** Provide at least one accessible passenger drop-off and loading zone complying with CBC 11B-503 at vehicle drop-off and vehicle pick-up areas. (CBC11B-209.2.1)

#### General Requirements: (CBC 11B-503)

- Vehicle Pull-up Space:** 8'-0" wide minimum x 20'-0" long minimum
- Access Aisle:** 5'-0" wide minimum x 20'-0" long minimum adjacent and parallel to the vehicle pull-up space. Access aisle shall adjoin an accessible route and shall not overlap the vehicle's pathway.
- Marking:** Access aisle shall be marked with a painted borderline around the perimeter. The area within the borderlines shall be marked with hatched lines a maximum of 36" on center in a color contrasting with that of the aisle surface.
- Slope:** Max 1:48 in all directions.



**FIGURE: PASSENGER DROP OFF AND LOADING ZONE ACCESS AISLE**